



## A54B4S11

|                                       |                                  |                |
|---------------------------------------|----------------------------------|----------------|
| Product                               | Rocker Switch                    |                |
| Serial                                | A54 Series                       |                |
| Connection / Nominal Dimension        | 30*22mm                          |                |
| Body Color                            | Black Body                       |                |
| Contact                               | 2NO                              |                |
| Illumination                          | with Illumination                |                |
| Connection Type                       | with Screw                       |                |
| Print                                 | (0-I) Marked                     |                |
| Color                                 | Yellow                           |                |
| Current                               | Ie                               | 16 A (250V AC) |
| Usage Category                        | AC15                             |                |
| Mechanical Life (Min Qty)             | 50000                            |                |
| Electrical Life (Min Qty)             | 50000                            |                |
| Operating Frequency (On-Off/Hour)     | Mech.900 Elec.900                |                |
| Insulation Voltage (Ui)               | 300 V                            |                |
| Impulse Withstand Voltage (Uimp)      | 2.5 kV                           |                |
| Dielectric Strength (Body-Contact)    | 2.500V AC                        |                |
| Dielectric Strength (Contact-Contact) | 1.500V AC                        |                |
| Isolation Resistance                  | 10 MΩ min. (500V DC)             |                |
| Operating Temperature                 | -15 / +80 °C                     |                |
| Pollution Degree                      | 3                                |                |
| Protection Degree                     | IP65                             |                |
| Contact Material                      | AgNi                             |                |
| Screw Torque                          | 1,5 Nm                           |                |
|                                       | 1 kA                             |                |
| Specifications                        | With or w/o illumination options |                |

Black or white body and 4 colour button options

**Standards / Certificates** TS EN 61058-1

