

**B160SL20K**

| | | |
|---------------------------------------|------------------------|-------------------------|
| Operating Current | | 5-20 mA (12-30V AC/DC) |
| Operational Frequency | | 50 Hz |
| Operational Voltage | | 12-30V AC/DC |
| Product | | Control Unit |
| Model | | Selector |
| Type | | Stay Put Illuminated |
| Label/Position | | (0-I) 60° |
| Contact | | 1NO |
| Color | | Red |
| Illumination | | with LED |
| Dia | | 22 mm |
| Current | I_e | 4 A (250V AC) |
| Usage Category | | AC 15 |
| Power Consumption | | 0.7 W |
| Mechanical Life | Min Qty | 500000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 3000 Elec. 1200 |
| Insulation Voltage | U_i | 300V |
| Impulse Withstand Voltage | U_{imp} | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ min. (500V DC) |
| Operating Temperature | | -15 / + 70 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP50 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1,5 Nm |

| | | |
|---|--|------|
| Short Circuit Breaking Capacity | Ics | 1 kA |
| Production Time | 31.12.1899 00:00:00 | |
| Serial | B Series Plastic | |
| Specifications | Non-flammable V0 PA6.6 contact blocks | |
| | Various illumination contact blocks availability | |
| | Variety of products for all areas of application | |
| Standards / Certificates | IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660 | |
|     | | |

