

CM101K20BB12

Print	(I-II) Marked
Product	Control Unit
Model	Double
Type	Flush
Contact	2NO
Color	White-White
Dia	22 mm
Current	I_e 4 A (230V AC)
Usage Category	AC 15
Mechanical Life	Min Qty 500000
Electrical Life	Min Qty 100000
Operating Frequency	On-Off/Hour Mech. 1200 Elec. 1200
Insulation Voltage	U_i 300V
Impulse Withstand Voltage	U_{imp} 2.5 kV
Dielectric Strength (Body-Contact)	2.500V AC
Dielectric Strength (Contact-Contact)	1.500V AC
Isolation Resistance	10 MΩ min. (500V DC)
Operating Temperature	-15 / + 65 °C
Pollution Degree	3
Protection Degree	IP65
Contact Material	AgNi
Cable Section	1.5-2.5 mm ²
Screw Torque	1,5 Nm
Short Circuit Breaking Capacity	I_{cs} 1 kA
Production Time	31.12.1899 00:00:00
Serial	CM Series Metal
Specifications	Die cast metal construction for harsh environment, corrosion-resistant chromate plating

	Non-flammable V0 PA6.6 contact blocks			
	Various illumination contact blocks availability			
	Variety of products for all areas of application			
	IP65 protection from front side			
Standards / Certificates	IEC 60947-5-1	TS EN 60947-5-1	UL 508	VDE 0660
   				