

D100YS21

Product	Control Unit	
Model	Selector	
Type	Stay Put	
Label/Position	(0-I) 60°	
Contact	1NO	
Dia	16 mm	
Head Type	Round	
Current	I _e	1,5 A (240V AC)
Usage Category	AC 15	
Mechanical Life	Min Qty	500000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 1200 Elec. 1200
Insulation Voltage	U _i	250V
Impulse Withstand Voltage	U _{imp}	2.5 kV
Dielectric Strength (Body-Contact)	2.500V AC	
Dielectric Strength (Contact-Contact)	1.500V AC	
Isolation Resistance	10 MΩ min. (500V DC)	
Operating Temperature	-15 / + 80 °C	
Pollution Degree	3	
Protection Degree	IP50	
Contact Material	AgNi	
Cable Section	Terminal 2,8x0,5	
Short Circuit Breaking Capacity	I _{cs}	1 kA
Production Time	31.12.1899 00:00:00	
Serial	D Series Plastic	
Specifications	Non-flammable V0 PA6.6 contact blocks	
	Various illumination contact blocks availability	
	Variety of products for all areas of application	

Ease of use in limited spaces
Standards / Certificates
IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660
  





Montaj Ölçüsü $\varnothing 16.3 \pm 0.2$ mm

Devre Şeması

