

D101DDK


Product		Control Unit
Model		Spring
Type		Flush
Contact		2NO
Color		Red
Dia		16 mm
Head Type		Rectangular
Current	I _e	1,5 A (240V AC)
Usage Category		AC 15
Mechanical Life	Min Qty	500000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 3000 Elec. 1200
Insulation Voltage	U _i	250V
Impulse Withstand Voltage	U _{imp}	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ min. (500V DC)
Operating Temperature		-15 / + 80 °C
Pollution Degree		3
Protection Degree		IP50
Contact Material		AgNi
Cable Section		Terminal 2,8x0,5
Short Circuit Breaking Capacity	I _{cs}	1 kA
Production Time		31.12.1899 00:00:00
Serial		D Series Plastic
Specifications		Non-flammable V0 PA6.6 contact blocks
		Various illumination contact blocks availability
		Variety of products for all areas of application

Ease of use in limited spaces
Standards / Certificates
IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660
  





Montaj Ölçüsü $\varnothing 16.3 \pm 0.2$ mm



Devre Şeması

3 ——— / ——— 4

3 ——— / ——— 4