

## L22M13

|                                       |                                 |
|---------------------------------------|---------------------------------|
| Product                               | Body + Contac Block             |
| Serial                                | Spare Part                      |
| Related Product                       | L22                             |
| Contact Action                        | Snap Action                     |
| Contact                               | 1NC+1NO                         |
| Current (Ie)                          | 3 A (240V AC)                   |
| Usage Category                        | AC15                            |
| Mechanical Life (Min Qty)             | 10000000                        |
| Electrical Life (Min Qty)             | 1000000                         |
| Operating Frequency (On-Off/Hour)     | Mech. 3000 Elec. 1800           |
| Insulation Voltage (Ui)               | 300 V                           |
| Impulse Withstand Voltage (Uimp)      | 2.5 kV                          |
| Dielectric Strength (Body-Contact)    | 1.890V AC                       |
| Dielectric Strength (Contact-Contact) | 1.890V AC                       |
| Isolation Resistance                  | 10 MΩ (500 V DC)                |
| Operating Temperature                 | -25 / + 80 °C                   |
| Pollution Degree                      | 3                               |
| Contact Material                      | AgNi                            |
| Cable Section                         | 1-2.5 mm <sup>2</sup>           |
| Screw Torque                          | 1.5Nm                           |
|                                       | 1 kA                            |
| Specifications                        | Plastic Body                    |
| Standards / Certificates              | TS EN 60947-5-1 UL 508 VDE 0663 |