



MB100HK

| | | |
|---------------------------------------|---------------------------------------|-----------------------|
| Product | Control Unit | |
| Model | Spring | |
| Type | Extended | |
| Contact | 1NO | |
| Color | Red | |
| Dia | 22 mm | |
| Current | Ie | 3 A (240V AC) |
| Usage Category | AC 15 | |
| Mechanical Life | Min Qty | 300000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 3000 Elec. 1200 |
| Insulation Voltage | Ui | 250V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | 2.500V AC | |
| Dielectric Strength (Contact-Contact) | 1.500V AC | |
| Isolation Resistance | 10 MΩ Min. (500 V DC) | |
| Operating Temperature | -15 / + 80 °C | |
| Pollution Degree | 3 | |
| Protection Degree | IP50 | |
| Contact Material | AgNi | |
| Cable Section | 1.5-2.5 mm ² | |
| Screw Torque | 1,5 Nm | |
| Short Circuit Breaking Capacity | Ics | 1 kA |
| Production Time | 31.12.1899 00:00:00 | |
| Serial | MB Series Plastic | |
| Specifications | Non-flammable V0 PA6.6 contact blocks | |
| | Monoblock strong body | |
| | Finger safe protection | |

Standards / Certificates IEC 60947-5-1 TS EN 60947-5-1

