



PDKA22GG20

Carton Box pieces

Qty 1

Product

Foot Switch

Model

with Hole for Metal Bar

Feature

Double

Contact

2*(1NO+1NC)+2*(1NO+1NC)

Color

Yellow

Protection

Metal Protection

Current

Ie 3 A (240V AC)

Usage Category

AC15

Mechanical Life

Min Qty 1000000

Electrical Life

Min Qty 100000

Operating Frequency

On-Off/Hour Mech. 1800 Elec. 1200

Insulation Voltage

Ui 300 V

Impulse Withstand Voltage

Uimp 2.5 kV

Dielectric Strength (Body-Contact)

2.500V AC

Dielectric Strength (Contact-Contact)

1.500V AC

Isolation Resistance

10 MΩ min. (500V DC)

Operating Temperature

-25 / +80 °C

Pollution Degree

3

Protection Degree

IP65

Contact Material

AgNi

Cable Section

1.5-2.5 mm²

Screw Torque

1.5Nm

Short Circuit Breaking Capacity

Ics 1 kA

Body Material

Plastic

Production Time

31.12.1899 00:00:00

Serial

PDK Series

Step

Double Step

Specifications	Plastic or Metal options
	Single and Double Speed
	Yellow
	Grey and orange color options
	with Latching option
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660
  	

PDKA22GG20

