





PDNS11GX10		
Carton Box pieces	**Qty**	1
Product		Foot Switch
Feature		Single
Contact		2*(1NO+1NC)
Color		Yellow
Protection		w/o Protection
Current	**Ie**	3 A (240V AC)
Usage Category		AC15
Mechanical Life	**Min Qty**	1000000
Electrical Life	**Min Qty**	100000
Operating Frequency	**On-Off/Hour**	Mech. 1800 Elec. 1200
Insulation Voltage	**Ui**	300 V
Impulse Withstand Voltage	**Uimp**	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ min. (500V DC)
Operating Temperature		-25 / +80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1.5-2.5 mm2
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	**Ics**	1 kA
Body Material		Plastic
Production Time		31.12.1899 00:00:00
Serial		PDN Series
Specifications	Plastic or Metal options	
	Single and Double Speed	

	Yellow
	Grey and orange color options
	with Latching option
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660
	

PDNS11GX10



K13
Devre Şeması



K13
Devre Şeması

