

## PSA020MS336SQ

|                                       |             |                                                 |
|---------------------------------------|-------------|-------------------------------------------------|
| Product                               |             | Cam Switch                                      |
| Feature                               |             | Yayli Geri Dönüş                                |
| Mounting                              |             | Quickmount                                      |
| Label/Position                        |             | (1-0-2)                                         |
| Switch Type                           |             | inverter                                        |
| Pole / Phase                          |             | 3 Phase                                         |
| Frame Size                            |             | 48*48                                           |
| Current                               | Ie          | 20A                                             |
| Usage Category                        |             | AC21A                                           |
| Mechanical Life                       | Min Qty     | 100000                                          |
| Electrical Life                       | Min Qty     | 50000                                           |
| Operating Frequency                   | On-Off/Hour | Mech.120 Elec.120                               |
| Insulation Voltage                    | Ui          | 690V                                            |
| Impulse Withstand Voltage             | Uimp        | 4 kV                                            |
| Dielectric Strength (Body-Contact)    |             | 1.890V AC                                       |
| Dielectric Strength (Contact-Contact) |             | 1.890V AC                                       |
| Isolation Resistance                  |             | 10 MΩ MIN. (500 V DC)                           |
| Operating Temperature                 |             | -25 / +80 °C                                    |
| Pollution Degree                      |             | 3                                               |
| Protection Degree                     |             | IP54                                            |
| Contact Material                      |             | AgNi                                            |
| Cable Section                         |             | 1-2,5 mm <sup>2</sup>                           |
| Spin Angle                            |             | 60°                                             |
| Short Circuit Breaking Capacity       | Ics         | 6 kA                                            |
| Serial                                |             | PSA Series                                      |
| Specifications                        |             | High precision                                  |
|                                       |             | Variety of products for wide application fields |
|                                       |             | Long life time                                  |

Compact design

Standards / Certificates

TS EN 60947-3

