



| | | |
|--|---|-------------------------|
| PV3T1X | | |
| Product | | Crane Pendant Station |
| Type | | 3 Hole |
| Current | Ie | 4A (250V AC) |
| Usage Category | | AC15 |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 900 Elec. 900 |
| Insulation Voltage | Ui | 300 V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ (500 V DC) |
| Operating Temperature | | -15 / + 80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP65 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1.5Nm |
| Short Circuit Breaking Capacity | Ics | 1kA |
| Serial | | PV Series |
| Speed | | Blank |
| 1.Hole | | Blind Cap |
| Specifications | Aesthetic look and ergonomic usage with assistance of ABS reinforced material | |
| | Mechanical interlock | |
| | Single and double speed | |
| Standards / Certificates | TS EN 60947-5-1 UL 508 VDE 0660 | |

CE

ERT



PV3T1X

