


PV5E40C22

| | | |
|--|---|---------------------|
| Product | Crane Pendant Station | |
| Type | 5 Hole | |
| Contact | 1NC+1NO | |
| Current | I_e | 4A (250V AC) |
| Usage Category | AC15 | |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 900 Elec. 900 |
| Insulation Voltage | U_i | 300 V |
| Impulse Withstand Voltage | U_{imp} | 2.5 kV |
| Dielectric Strength (Body-Contact) | 2.500V AC | |
| Dielectric Strength (Contact-Contact) | 1.500V AC | |
| Isolation Resistance | 10 MΩ (500 V DC) | |
| Operating Temperature | -15 / + 80 °C | |
| Pollution Degree | 3 | |
| Protection Degree | IP65 | |
| Contact Material | AgNi | |
| Cable Section | 1.5-2.5 mm ² | |
| Screw Torque | 1.5Nm | |
| Short Circuit Breaking Capacity | I_{cs} | 1kA |
| Serial | PV Series | |
| Speed | Single Speed | |
| 1.Hole | Emergency Stop | |
| Specifications | Aesthetic look and ergonomic usage with assistance of ABS reinforced material | |
| | Mechanical interlock | |
| | Single and double speed | |
| Standards / Certificates | TS EN 60947-5-1 UL 508 VDE 0660 | |

CE

ERT



PV5E40C22

