

**PV5EA30B44**

Product		Crane Pendant Station
Type		5 Hole
Contact		1NC
Current	Ie	4A (250V AC)
Usage Category		AC15
Mechanical Life	Min Qty	1000000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 900 Elec. 900
Insulation Voltage	Ui	300 V
Impulse Withstand Voltage	Uimp	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ (500 V DC)
Operating Temperature		-15 / + 80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1.5-2.5 mm ²
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	Ics	1kA
Production Time		15.08.2022 00:00:00
Serial		PV Series
Speed		Double Speed
1.Hole		Emergency Stop Turn to Release with Key Operated
Specifications		Aesthetic look and ergonomic usage with assistance of ABS reinforced material
		Mechanical interlock

Single and double speed

Standards / Certificates TS EN 60947-5-1 UL 508 VDE 0660

