



### PV9E30B222AC20

|  |   |                     |
|--|---|---------------------|
| <b>Product</b>                               | Crane Pendant Station   |                     |
| <b>Type</b>                                  | 9 Hole  |                     |
| <b>Contact</b>                               | 1NC   |                     |
| <b>Current</b>                               | <b>Ie</b>   | 4A (250V AC)        |
| <b>Usage Category</b>                        | AC15  |                     |
| <b>Mechanical Life</b>                       | <b>Min Qty</b>  | 1000000             |
| <b>Electrical Life</b>                       | <b>Min Qty</b>  | 100000              |
| <b>Operating Frequency</b>                   | <b>On-Off/Hour</b>  | Mech. 900 Elec. 900 |
| <b>Insulation Voltage</b>                    | <b>Ui</b>   | 300 V               |
| <b>Impulse Withstand Voltage</b>             | <b>Uimp</b>   | 2.5 kV              |
| <b>Dielectric Strength (Body-Contact)</b>    | 2.500V AC   |                     |
| <b>Dielectric Strength (Contact-Contact)</b> | 1.500V AC   |                     |
| <b>Isolation Resistance</b>                  | 10 MΩ (500 V DC)  |                     |
| <b>Operating Temperature</b>                 | -15 / + 80 °C   |                     |
| <b>Pollution Degree</b>                      | 3   |                     |
| <b>Protection Degree</b>                     | IP65  |                     |
| <b>Contact Material</b>                      | AgNi  |                     |
| <b>Cable Section</b>                         | 1.5-2.5 mm <sup>2</sup>   |                     |
| <b>Screw Torque</b>                          | 1.5Nm   |                     |
| <b>Short Circuit Breaking Capacity</b>       | <b>Ics</b>  | 1kA                 |
| <b>Serial</b>                                | PV Series   |                     |
| <b>Speed</b>                                 | Single Speed  |                     |
| <b>1.Hole</b>                                | Key Selector  |                     |
| <b>Specifications</b>                        | Aesthetic look and ergonomic usage with assistance of ABS reinforced material |                     |
|  | Mechanical interlock  |                     |
|  | Single and double speed   |                     |
| <b>Standards / Certificates</b>              | TS EN 60947-5-1 UL 508 VDE 0660   |                     |

CE

ERT

