

**PY336E36E13G**

Product	Control Box
Color	Black-Grey
Current	<b>Ie</b> 4A (250V AC)
Usage Category	AC15
Mechanical Life	<b>Min Qty</b> 1000000
Electrical Life	<b>Min Qty</b> 100000
Operating Frequency	<b>On-Off/Hour</b> Mech. 3000 Elec. 1200
Insulation Voltage	<b>Ui</b> 300 V
Impulse Withstand Voltage	<b>Uimp</b> 2.5 kV
Dielectric Strength (Body-Contact)	2.500V AC
Dielectric Strength (Contact-Contact)	1.500V AC
Isolation Resistance	10 M $\Omega$ (500 V DC)
Operating Temperature	-15 / + 80 °C
Pollution Degree	3
Protection Degree	IP65
Contact Material	AgNi
Cable Section	1.5-2.5 mm <sup>2</sup>
Screw Torque	1.5Nm
Short Circuit Breaking Capacity	<b>Ics</b> 1kA
Production Time	12.08.2022 00:00:00
Serial	PY Series Plastic
Hole Qty	3 Holes
Ingredients	CP200EA30 + 2*CM100DHOD
Specifications	Suitable for $\varnothing$ 22 mm buttons
	Strong resistance against mechanical strokes
	IP65 with suitable buttons
	Body types in different dimensions
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660

CE

