

**RE2.I20.AC230.S0**

| | |
|--|--|
| Product | PCB Power Relay |
| Serial | RE2 Series |
| Contact | 2NO+0NC |
| Pin | 6Pin |
| Contact Material | AgNi 90/10 |
| Pin Pitch (mm) | 5mm Pin Pitch |
| | 3.5x0.8mm |
| Connection Type | PCB |
| Operational Voltage | 230VAC |
| Current (Ie) | 8A |
| Voltage | 250V AC |
| Usage Category | AC-1 |
| Mechanical Life (Min Qty) | 5000000 |
| Electrical Life (Min Qty) | 30000 |
| Dielectric Strength (Body-Contact) | 5.000 Vrms |
| Dielectric Strength (Contact-Contact) | 1.000 Vrms |
| Operating Temperature | -40 / +70 °C |
| Pollution Degree | 2 |
| Protection Degree | WT |
| Weight (Net) (Gr) | 14 |
| Specifications | Flux Proof |
| | High mechanical and electrical endurance for continuous operation |
| | Compact design ideal for panel builders and machine manufacturers |
| | Modüler konsept soket, röle, modül |
| | Compatible with standard relay sockets |
| | Exceptional performance even in demanding industrial environments |
| | Application: Panel Board, Mechanical engineering, machine industry |
| Standards / Certificates | TS EN 61810-1 |

