

**RE2.I2C.DC048.S0**

<b>Product</b>	PCB Power Relay
<b>Serial</b>	RE2 Series
<b>Contact</b>	2CO
<b>Pin</b>	8Pin
<b>Contact Material</b>	AgNi 90/10
<b>Pin Pitch (mm)</b>	5mm Pin Pitch 3.5x0.8mm
<b>Connection Type</b>	PCB
<b>Operational Voltage</b>	48VDC
<b>Current (Ie)</b>	8A
<b>Voltage</b>	250V AC
<b>Usage Category</b>	AC-1
<b>Mechanical Life (Min Qty)</b>	30000000
<b>Electrical Life (Min Qty)</b>	100000
<b>Dielectric Strength (Body-Contact)</b>	5.000 Vrms
<b>Dielectric Strength (Contact-Contact)</b>	1.000 Vrms
<b>Operating Temperature</b>	-40 / +80 °C
<b>Pollution Degree</b>	2
<b>Protection Degree</b>	WT
<b>Weight (Net) (Gr)</b>	13
<b>Specifications</b>	Wash Tight High mechanical and electrical endurance for continuous operation Compact design ideal for panel builders and machine manufacturers Modüler konsept soket, röle, modül Compatible with standard relay sockets Exceptional performance even in demanding industrial environments Application: Panel Board, Mechanical engineering, machine industry
<b>Standards / Certificates</b>	TS EN 61810-1

