

**RE2.P3C.AC115.L0**

<b>Product</b>	Power Relay
<b>Serial</b>	RE2 Series
<b>Contact</b>	3CO
<b>Pin</b>	11Pin
<b>Contact Material</b>	AgNi 90/10
<b>Pin Pitch (mm)</b>	5mm Pin Pitch
<b>Feature</b>	with LED
	6x2.2mm
<b>Connection Type</b>	Plug-in
<b>Operational Voltage</b>	115VAC
<b>Current (Ie)</b>	10A
<b>Voltage</b>	250V AC
<b>Usage Category</b>	AC-1
<b>Mechanical Life (Min Qty)</b>	20000000
<b>Electrical Life (Min Qty)</b>	100000
<b>Dielectric Strength (Body-Contact)</b>	2.500Vrms
<b>Dielectric Strength (Contact-Contact)</b>	1.200 Vrms
<b>Operating Temperature</b>	-40 / +70 °C
<b>Pollution Degree</b>	2
<b>Protection Degree</b>	FP
<b>Weight (Net) (Gr)</b>	30
<b>Specifications</b>	Flux Proof
	High mechanical and electrical endurance for continuous operation
	Compact design ideal for panel builders and machine manufacturers
	Transparent housing for easy visual inspection
	Manual test button and mechanical indicator
	Compatible with standard relay sockets
	Exceptional performance even in demanding industrial environments
	Sensitive Coil

Optional LED

Application: Machine industry, Elevator industry, Building management

**Standards / Certificates**

TS EN 61810-1

