

| | | |
|---|---|---|
| **SKF1A-1D** | | |
| **Product** | | Level Control Float Switch |
| **Type** | | Bulb |
| **Feature** | | With Diamond Weight |
| **Cable** | | 1m |
| **Phase Number** | | 1 Phase |
| **Current** | **Ie** | 6 A (250V AC) |
| **Usage Category** | | AC15 |
| **Mechanical Life** | **Min Qty** | 30000 |
| **Electrical Life** | **Min Qty** | 10000 |
| **Operating Frequency** | **On-Off/Hour** | Mek.120 Elk.120 |
| **Insulation Voltage** | **Ui** | 660V |
| **Impulse Withstand Voltage** | **Uimp** | 2.75 kV |
| **Dielectric Strength (Body-Contact)** | | 2750V AC |
| **Dielectric Strength (Contact-Contact)** | | 1890V AC |
| **Isolation Resistance** | | 10 MΩ MİN. (500 V DC) |
| **Operating Temperature** | | -15 / + 80 °C |
| **Protection Degree** | | IP68 |
| **Contact Material** | | AgNi |
| **Cable Section** | | 3*1 mm Kablo |
| **Production Time** | | 1.03.2022 00:00:00 |
| **Serial** | | SKF1A Series |
| **Cable Type** | | PVC |
| **Specifications** | Easy assembly | |
| | Feature to adjust the requested operation interval with weight | |
| | Different cable lenghth options | |
| | Waterproof | |
| **Standards / Certificates** | TS EN 60730-2-15 | |