



# ECE316V4PE

|                                       |                   |                       |
|---------------------------------------|-------------------|-----------------------|
| Operating Current                     |                   | 16A                   |
| Product                               |                   | CEE Norm              |
| Type                                  |                   | Angled Type Socket    |
| Contact                               |                   | 2+Neutral             |
| Mechanical Life                       | Min Qty           | ≥ 500                 |
| Electrical Life                       | Min Qty           | ≥ 100                 |
| Operating Frequency                   | On-Off/Hour       | Mech.240 Elec.120     |
| Insulation Voltage                    | Ui                | 690V                  |
| Impulse Withstand Voltage             | Uimp              | 6 kV                  |
| Dielectric Strength (Body-Contact)    |                   | 1890V AC              |
| Dielectric Strength (Contact-Contact) |                   | 3000V AC              |
| Isolation Resistance                  |                   | 10 MΩ Min. (500 V DC) |
| Operating Temperature                 |                   | -40 / +125 °C         |
| Pollution Degree                      |                   | 2                     |
| Protection Degree                     |                   | IP44                  |
| Body Material                         |                   | Plastic               |
| Production Time                       |                   | 12.07.1905 00:00:00   |
| Serial                                |                   | ECE Series            |
| Standards / Certificates              | TS 7205 EN60309-1 |                       |

