

# IF5T024ZM05-5

|                       |                                                          |                     |
|-----------------------|----------------------------------------------------------|---------------------|
| Operational Frequency |                                                          | 50 Hz               |
| Operational Voltage   |                                                          | 24V DC              |
| Product               |                                                          | LED Beacon 55mm     |
| Control               |                                                          | Key Control         |
| Mounting              |                                                          | M22 Screw           |
| Color                 |                                                          | Three Level         |
| Illumination          |                                                          | Constant            |
| Cable                 |                                                          | 5mt Cable           |
| Volume                |                                                          | 90 dB               |
| Insulation Voltage    | <b>Ui</b>                                                | 300V                |
| Operating Temperature |                                                          | -25 °C /+70 °C      |
| Protection Degree     |                                                          | IP65                |
| Cable Section         |                                                          | Cable 0,50 mm2      |
| Production Time       |                                                          | 31.12.1899 00:00:00 |
| Serial                |                                                          | IF Series           |
| Buzzer                |                                                          | With Buzzer         |
| Electrical Life       | <b>Min Hour</b>                                          | 10000               |
| Specifications        | Heat resistant, clear vision Polycarbonate signal module |                     |
|                       | Monoblock construction                                   |                     |
|                       | Easy wiring                                              |                     |
|                       | Easy to install to 22mm hole                             |                     |