

## IK73L024ZM02

|                            |   |                          |
|----------------------------|---|--------------------------|
| Weight (Gross with Carton) | Gr  | 425                      |
| Bulb Type                  |   | LED                      |
| Operational Frequency      |   | 50 Hz                    |
| Operational Voltage        |   | 24V AC/DC                |
| Product                    |   | LED Tower 70mm           |
| Mounting                   |   | 45mm Tube Plastic Base   |
| Color                      |   | Four Level               |
| Volume                     |   | 90 dB                    |
| Power Consumption          |   | 4W                       |
| Insulation Voltage         | Ui  | 300V                     |
| Operating Temperature      |   | -25 °C /+70 °C           |
| Protection Degree          |   | IP40                     |
| Cable Section              |   | 0,75-1,5 mm <sup>2</sup> |
| Screw Torque               |   | 1,8Nm                    |
| Lampholder Type            |   | BA15S                    |
| Production Time            |   | 31.12.1899 00:00:00      |
| Serial                     |   | IK Series                |
| Buzzer                     |   | With Buzzer              |
| Electrical Life            | Min Hour  | 10000                    |
| Specifications             | Heat resistant, clear vision Polycarbonate signal modules |                          |
|                            | Modular construction                                      |                          |
|                            | Easy wiring   |                          |
|                            | Variety of connection bases                               |                          |