

L51K25HUM112

Product	Limit Switch
Feature	With Reset
Contact	1NO+2NC
Actuator	Rope Pull Safety Switch
Current	I_e 3 A (240V AC)
Usage Category	AC15
Mechanical Life	Min Qty 10000000
Electrical Life	Min Qty 1000000
Operating Frequency	On-Off/Hour Mech. 3000 Elec. 1800
Insulation Voltage	U_i 300 V
Impulse Withstand Voltage	U_{imp} 2.5 kV
Dielectric Strength (Body-Contact)	1.890V AC
Dielectric Strength (Contact-Contact)	1.890V AC
Isolation Resistance	10 MΩ (500 V DC)
Operating Temperature	-25 / + 80 °C
Pollution Degree	3
Protection Degree	IP65
Contact Material	AgNi
Cable Section	1-2.5 mm ²
Screw Torque	1.5Nm
Short Circuit Breaking Capacity	I_{cs} 1 kA
Production Time	31.12.1899 00:00:00
Serial	L51 Metal Body
Contact Action	Slow Action
Actuator Material	Metal
Specifications	Metal Body and Cover
	1 side PG13,5 or M20x1,5 hole

Various actuator options with wide sensitive contact block alternatives for all kind of applications

Standards / Certificates TS EN 60947-5-1 UL 508 VDE 0660

