



L52K13MEP123

Product	Limit Switch	
Production Time	31.12.1899 00:00:00	
Serial	L52 Metal Body	
Contact Action	Snap Action	
Actuator Material	Plastic	
Short Circuit Breaking Capacity	Ics	1 kA
Screw Torque	1.5Nm	
Cable Section	1-2.5 mm ²	
Contact Material	AgNi	
Protection Degree	IP65	
Pollution Degree	3	
Operating Temperature	-25 / + 80 °C	
Isolation Resistance	10 MΩ (500 V DC)	
Dielectric Strength (Contact-Contact)	1.890V AC	
Dielectric Strength (Body-Contact)	1.890V AC	
Impulse Withstand Voltage	Uimp	2.5 kV
Insulation Voltage	Ui	300 V
Operating Frequency	On-Off/Hour	Mech. 3000 Elec. 1800
Electrical Life	Min Qty	1000000
Mechanical Life	Min Qty	10000000
Usage Category	AC15	
Current	Ie	3 A (240V AC)
Actuator Dia	18 mm	
Actuator	Adjustable Roller Arm	
Contact	1NO+1NC	
Specifications	Metal Body and Cover	
	1 side PG13,5 or M20x1,5 hole	

Various actuator options with wide sensitive contact block alternatives for all kind of applications

Standards / Certificates TS EN 60947-5-1 UL 508 VDE 0660

