



## PDKA22BB10

|                                       |             |                          |
|---------------------------------------|-------------|--------------------------|
| Carton Box pieces                     | Qty         | 1                        |
| Product                               |             | Foot Switch              |
| Model                                 |             | with Hole for Metal Bar  |
| Feature                               |             | Double                   |
| Contact                               |             | (1NO+1NC)+(1NO+1NC)      |
| Color                                 |             | Yellow                   |
| Protection                            |             | Metal Protection         |
| Current                               | Ie          | 3 A (240V AC)            |
| Usage Category                        |             | AC15                     |
| Mechanical Life                       | Min Qty     | 1000000                  |
| Electrical Life                       | Min Qty     | 100000                   |
| Operating Frequency                   | On-Off/Hour | Mech. 1800 Elec. 1200    |
| Insulation Voltage                    | Ui          | 300 V                    |
| Impulse Withstand Voltage             | Uimp        | 2.5 kV                   |
| Dielectric Strength (Body-Contact)    |             | 2.500V AC                |
| Dielectric Strength (Contact-Contact) |             | 1.500V AC                |
| Isolation Resistance                  |             | 10 MΩ min. (500V DC)     |
| Operating Temperature                 |             | -25 / +80 °C             |
| Pollution Degree                      |             | 3                        |
| Protection Degree                     |             | IP65                     |
| Contact Material                      |             | AgNi                     |
| Cable Section                         |             | 1.5-2.5 mm <sup>2</sup>  |
| Screw Torque                          |             | 1.5Nm                    |
| Short Circuit Breaking Capacity       | Ics         | 1 kA                     |
| Body Material                         |             | Plastic                  |
| Production Time                       |             | 31.12.1899 00:00:00      |
| Serial                                |             | PDK Series               |
| Specifications                        |             | Plastic or Metal options |

|                                                                                                                                                                                                                                                                                                                                                                         |                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
|                                                                                                                                                                                                                                                                                                                                                                         | Single and Double Speed               |
|                                                                                                                                                                                                                                                                                                                                                                         | Yellow                                |
|                                                                                                                                                                                                                                                                                                                                                                         | Grey and orange color options         |
|                                                                                                                                                                                                                                                                                                                                                                         | with Latching option                  |
|                                                                                                                                                                                                                                                                                                                                                                         | TS EN 60947-5-1    UL 508    VDE 0660 |
| <b>Standards / Certificates</b>     |                                       |